

ALLMAND 23 (HMS 23)

Sailboat Specifications

Hull Type:	Fin w/transom hung rudder		Rigging Type:	Cutter	
LOA:	23.00 ft / 7.01 m		LWL:	19.83 ft / 6.04 m	
Beam:	9.50 ft / 2.90 m		S.A. (reported):	211.00 ft ² / 19.60 m ²	
Draft (max):			2.50 ft / 0.76 m		
Displacement:	3,360 lb / 1,524 kg		Ballast:	600 lb / 272 kg	
S.A./Disp.:	15.09	Bal./Disp.:	17.86	Disp./Len.:	192.36
First Built:			1975		
Builder:			Allmand Boats Inc. (USA)		

Sailboat Calculations

S.A./Disp.:	15.09
Bal./Disp.:	17.86
Disp./Len.:	192.36
Comfort Ratio:	12.46
Capsizing Screening Formula:	2.54
S#:	2.55

Rig and Sail Particulars

I:	24.33 ft / 7.42 m	J:	10.14 ft / 3.09 m
P:	20.00 ft / 6.10 m	E:	8.75 ft / 2.67 m
S.A. Fore:	123.35 ft ² / 11.46 m ²	S.A. Main:	87.50 ft ² / 8.13 m ²
S.A. Total (100% Fore + Main Triangles)		210.85 ft ² / 19.59 m ²	
S.A./Disp. (calc.):	15.08	Est. Forestay Len.:	26.36 ft / 8.03 m

Sailboat Organizations

Builders:	Allmand Boats Inc.(USA)
Associations:	Allmand Owners

Additional Notes

Also called HMS 23.

Available with fixed or swing keel.

Inboard power available as an option.

Built in very small numbers.

Dimensions from builders literature.