



BUCCANEER 240

Sailboat Specifications

Hull Type:	Long keel w/trans. hung rudd	Rigging Type:	Masthead Sloop
LOA:	23.67 ft / 7.21 m	LWL:	20.33 ft / 6.20 m
Beam:	8.00 ft / 2.44 m	S.A. (reported):	248.00 ft ² / 23.04 m ²
Draft (max):		2.50 ft / 0.76 m	
Displacement:	4,000 lb / 1,814 kg	Ballast:	1,250 lb / 567 kg
S.A./Disp.:	15.79	Bal./Disp.:	31.25
		Disp./Len.:	212.52
First Built:		1975	
Builder:		Bayliner Marine Corp (USA)	
Designer:		Alan Payne/Bayliner	

Sailboat Calculations

S.A./Disp.:	15.79
Bal./Disp.:	31.25
Disp./Len.:	212.52
Comfort Ratio:	18.16
Capsizing Screening Formula:	2.02
S#:	2.20

Rig and Sail Particulars

I:	26.20 ft / 7.99 m	J:	9.33 ft / 2.84 m
P:	22.25 ft / 6.78 m	E:	8.75 ft / 2.67 m
S.A. Fore:	122.22 ft ² / 11.35 m ²	S.A. Main:	97.34 ft ² / 9.04 m ²
S.A. Total (100% Fore + Main Triangles)		219.57 ft ² / 20.40 m ²	
S.A./Disp. (calc.):	13.98	Est. Forestay Len.:	27.81 ft / 8.48 m
Mast Height from DWL:		33.83 ft / 10.31 m	

Sailboat Accommodations

Water:	20 gals / 76 L
---------------	----------------

Sailboat Organizations

Designers:	Alan Payne
Builders:	Bayliner (Buccaneer/US Yachts)

Additional Notes

This same yacht, but with a diesel inboard, was called the BUCCANEER 245. It is thought that the hull for the BUCCANEER 200, 210, 240, and 245 all derive from the COLUMBIA 23-T.

The number of windows (above and below the sheer line) doesn't appear to always be consistent for a particular model.

Alt. Tall Rig:

I: 30.10' / 9.17m

J: 9.50' / 2.90m

P: 26.30' / 8.02m

E: 8.75' / 2.67m