

# C&C 25

## Sailboat Specifications

<b>Hull Type:</b>	Fin w/transom hung rudder		<b>Rigging Type:</b>	Masthead Sloop	
<b>LOA:</b>	25.16 ft / 7.67 m		<b>LWL:</b>	20.67 ft / 6.30 m	
<b>Beam:</b>	8.58 ft / 2.62 m		<b>S.A. (reported):</b>	306.00 ft <sup>2</sup> / 28.43 m <sup>2</sup>	
<b>Draft (max):</b>			3.75 ft / 1.14 m		
<b>Displacement:</b>	4,300 lb / 1,950 kg		<b>Ballast:</b>	1,900 lb / 862 kg	
<b>S.A./Disp.:</b>	18.57	<b>Bal./Disp.:</b>	44.19	<b>Disp./Len.:</b>	217.37
<b>Ballast Type:</b>			lead		
<b>First Built:</b>			1973		
<b>Builder:</b>			C&C Yachts		
<b>Designer:</b>			C&C		

## Auxiliary Power/Tanks (orig. equip.)

<b>Make:</b>	Inboard, Saildrive or OB	<b>Model:</b>	Vire
<b>Type:</b>	Gas	<b>HP:</b>	7

## Sailboat Calculations

<b>S.A./Disp.:</b>	18.57
<b>Bal./Disp.:</b>	44.19
<b>Disp./Len.:</b>	217.37
<b>Comfort Ratio:</b>	17.23
<b>Capsize Screening Formula:</b>	2.11
<b>S#:</b>	2.67

## Rig and Sail Particulars

<b>I:</b>	31.50 ft / 9.60 m	<b>J:</b>	11.00 ft / 3.35 m
<b>P:</b>	26.50 ft / 8.08 m	<b>E:</b>	10.00 ft / 3.05 m
<b>S.A. Fore:</b>	173.25 ft <sup>2</sup> / 16.10 m <sup>2</sup>	<b>S.A. Main:</b>	132.50 ft <sup>2</sup> / 12.31 m <sup>2</sup>
<b>S.A. Total (100% Fore + Main Triangles)</b>	305.75 ft <sup>2</sup> / 28.41 m <sup>2</sup>		
<b>S.A./Disp. (calc.):</b>	18.55	<b>Est. Forestay Len.:</b>	33.37 ft / 10.17 m

## Sailboat Accommodations

<b>Water:</b>	10 gals / 38 L
---------------	----------------

## Sailboat Organizations

<b>Designers:</b>	C&C Design
<b>Builders:</b>	C&C Yachts

## Additional Notes

Replaced with the C&C 25 MKII in 1982, a completely new design.