

STONE HORSE 26

Sailboat Specifications

Hull Type:	Long keel w/trans. hung rudd	Rigging Type:	Cutter		
LOA:	28.25 ft / 8.61 m	LWL:	18.33 ft / 5.59 m		
Beam:	7.08 ft / 2.16 m	S.A. (reported):	339.00 ft ² / 31.49 m ²		
Draft (max):		3.58 ft / 1.09 m			
Displacement:	4,490 lb / 2,037 kg	Ballast:	2,000 lb / 907 kg		
S.A./Disp.:	19.99	Bal./Disp.:	44.54	Disp./Len.:	325.47
Ballast Type:		Lead			
First Built:	1931	# Built:	150		
Builder:		Edey & Duff (USA)			
Designer:		S. S. Crocker 1931			

Auxiliary Power/Tanks (orig. equip.)

Make:	Westerbeke	Model:	Vire
Type:	Gas	HP:	6
Fuel:		5 gals / 19 L	

Sailboat Calculations

S.A./Disp.:	19.99
Bal./Disp.:	44.54
Disp./Len.:	325.47
Comfort Ratio:	24.00
Capsize Screening Formula:	1.72
S#:	1.67

Rig and Sail Particulars

I:	28.50 ft / 8.69 m	J:	10.50 ft / 3.20 m
P:	25.75 ft / 7.85 m	E:	12.83 ft / 3.91 m
S.A. Fore:	149.63 ft ² / 13.90 m ²	S.A. Main:	165.19 ft ² / 15.35 m ²
S.A. Total (100% Fore + Main Triangles)	314.81 ft ² / 29.25 m ²		
S.A./Disp. (calc.):	18.56	Est. Forestay Len.:	30.37 ft / 9.26 m
Mast Height from DWL:	32.33 ft / 9.85 m		

Sailboat Accommodations

Water:	12 gals / 45 L
---------------	----------------

Sailboat Organizations

Designers:	Samuel Crocker
Builders:	Edey & Duff (USA)

Additional Notes

Hull Length: 23.33 ft

At least 30 built of wood since 1931. Adapted for Fiberglass construction in 1968.(Edey & Duff).